

1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com


PRODUCT INFORMATION

GRAINING BASE

PRODUCT NO.	202, 203, 212, 213, 214
GENERIC TYPE	Eggshell finish oil base paint
COLOR	5 Ready-mixed colors
GLOSS	20-25 @ 60°
SOLIDS BY WEIGHT	70-72%
SOLIDS BY VOLUME	50-53%
V.O.C.	380 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	815-840 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	400-450 sq. ft.
RECOMMENDED DFT PER COAT	1½ Mils
WEIGHT PER GALLON	10.6-11.0 lbs.
FLASH POINT	102°F Tag Closed Cup
USE	Alone as an eggshell enamel, as a tint base, or as the foundation coat in our exclusive woodgraining process.
VISCOSITY AT 77° F	72 - 74 Kneb Units
AVERAGE DRY TIME AT 70°F & 50% R.H.	8-10 hours, depending upon humidity and temperature.
RECOMMENDED THINNER	Do not thin.
APPLICATION	Brush, roller, or sprayer application.
SURFACE PREPARATION	The surface must be clean, smooth and free from dust, dirt, wax, and grease.
CLEAN-UP	Mineral Spirits
COMPOSITION	By colors upon request - colors are:
	Driftwood 20201
	Walnut 20301
	Maple 21201
	Pine 21301
	Mahogany 21401

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

GRAINING BASE

DESCRIPTION: OLD MASTERS® GRAINING BASE, a high quality, interior, eggshell finish oil base paint, can be used alone or under our WIPING STAIN to achieve a wide variety of distinctive decorating effects. GRAINING BASE, when used as the first step in woodgraining, approximates both the texture and color of bare or unfinished wood. With GRAINING BASE, any interior surface that can be painted can be grained—new wood, previously finished surfaces, cabinets, furniture, bookshelves or metal doors—without the added work of stripping old finishes. GRAINING BASE does not raise the wood grain, as do many latex base paints, and provides excellent durability and chip resistance on high-use interior surfaces. GRAINING BASE is non-toxic when dry, and is safe for children's furniture.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: The surface must be clean, dry and free from any dirt, wax or grease. Sand new wood thoroughly, then remove dust particles with a lint-free rag or tack rag. On previously finished surfaces, the old finish need not be removed if in sound condition. For metal surfaces, or high gloss finishes, first remove gloss by sanding to roughen surface and ensure adhesion, then remove all dust particles with a tack rag.

DIRECTIONS FOR APPLICATION: Stir thoroughly, before and during use. Apply with a good-quality, natural bristle brush or use spray application. If applying to metal surfaces, such as doors, apply GRAINING BASE in the direction of the intended wood grain. Should a second coat be desired, allow first coat to dry for 24 hours, sand surface lightly, then recoat. Also allow 24 hours drying time prior to applying WIPING STAIN to achieve a woodgrain effect.

SPREADING RATE: Approximately 100 square feet per quart.

DRYING TIME: GRAINING BASE will dry to touch in 8 to 10 hours, depending on humidity and temperature. A second coat may be applied, if desired, after 24 hours. If applying a WIPING STAIN to achieve a woodgrain look, allow surface to dry thoroughly (about 24 hours) prior to stain application. High humidity or low temperature will extend drying time.

CLEAN UP: Clean up your brushes with mineral spirits or paint thinner.

MAX. VOC: 380 grams/liter (3.2 lbs./gal.)

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041