



1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-737-3436 Fax 712-737-3893  
www.oldmastrs.com

## PRODUCT INFORMATION

### PERFECT MATCH® WIPING STAIN TINT BASE

<b>PRODUCT NO.</b>	51001, 51004
<b>GENERIC TYPE</b>	Neutral Base Tint Base (Wiping Stain Formula)
<b>COLOR</b>	Clear
<b>GLOSS</b>	N/A
<b>SOLIDS BY WEIGHT</b>	36-37%
<b>SOLIDS BY VOLUME</b>	30-31%
<b>VOC</b>	550 grams/liter
<b>SPREADING RATE</b>	300-500 sq. ft. per gal.
<b>WEIGHT PER GALLON</b>	7.2-7.3 lbs.
<b>FLASH POINT</b>	102° F.
<b>USE</b>	A tint base formulated for the creation of custom stain colors using universal colorants. For staining bare wood, or as a glaze for creating faux finishes.
<b>VISCOSITY AT 77° F.</b>	400-500 CPS
<b>AVERAGE DRY TIME AT 70°F. &amp; 50% R.H.</b>	10-12 hours
<b>RECOMMENDED THINNER</b>	Do not thin.
<b>APPLICATION</b>	Apply with brush, lint-free cloth, or sprayer.
<b>SURFACE PREPARATION</b>	The wood surface must be sound, dry, and free from dust, dirt, wax or grease. Sand the wood thoroughly, first with a medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag.
<b>MIXING INSTRUCTIONS</b>	CUSTOM TINTING: Up to 10 ounces of universal colorant may be added per gallon. The product is short-filled in the can to allow room for the appropriate amount of colorant. The amount of colorant added may affect its performance and extend the dry time.
<b>CLEAN-UP</b>	Mineral spirits

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



## PRODUCT INFORMATION

### **PERFECT MATCH® WIPING STAIN TINT BASE**

**DESCRIPTION:** OLD MASTERS® PERFECT MATCH® WIPING STAIN TINT BASE is specifically formulated for the creation of custom colors using universal colorants. This allows the user to receive all the benefits of unlimited color choice with the outstanding versatility of WIPING STAIN's full-bodied formulation. WIPING STAIN is slow drying, oil based, and semi-transparent for interior applications. Its thick, rich formula allows it to achieve limitless decorating possibilities when used either as a stain or as a glaze over any of the Old Masters® GRAINING BASES.

**CUSTOM TINTING:** Up to 10 ounces of universal colorant may be added per gallon. The product is short-filled in the can to allow room for the appropriate amount of colorant. The amount of colorant added may affect its performance and extend the dry time.

**THINNING:** Do not thin. Use as packaged.

**SURFACE PREPARATION:** The secret to successful applications is a properly prepared surface. All surfaces must be sound, dry, and free from dust, dirt, wax, or grease. Surface defects should be repaired with an appropriate patching material.

**APPLICATION ON BARE WOOD (used as a stain):** Color of stain will vary depending on wood type and porosity, and the method of application. Always test stain in an inconspicuous area. Stir well before and during application for even distribution of color. After cleaning wood surface, sand with #120 or #180 sandpaper until smooth, then remove sanding dust. Apply stain liberally with brush, lint-free cloth, or spray until surface is completely wet. Allow to penetrate for 5 to 15 minutes. Then wipe with a soft cloth, first across the grain, then with

the grain. For a darker color, restain when first coat is dry. For a lighter color, wipe with a cloth dampened with paint thinner before the stain has dried. Before applying a clear finish, allow the stain to dry thoroughly.

**APPLICATION OVER GRAINING BASE (used as a glaze):** Apply to thoroughly dry paint with cheesecloth or brush, using long smooth strokes for simulated woodgraining, or blend gently from edges for other effects. Allow stain to set up approximately 5 to 10 minutes, then dry brush to subdue or blend. Allow stain to dry thoroughly (usually 12 hours or longer, depending on humidity and drying conditions). Apply a clear finish when stain is thoroughly dry. We do not recommend a lacquer-type finish over a glaze application.

**SPREADING RATE:** Approximately 500 square feet per gallon. Spreading rate will vary significantly depending on application method and condition of wood.

**DRYING TIME:** Approximately 10 hours, depending on humidity, temperature, and use of product (as a stain or glaze). WIPING STAIN can be topcoated after 12 hours, but stain must be thoroughly dry.

**CLEAN UP:** Use mineral spirits or paint thinner. Take precautions: oily rags should be promptly discarded into a water-filled container to reduce the risk of spontaneous combustion.

**RECOMMENDED FINISH COAT:** We recommend OLD MASTERS® clear finishes. However, our WIPING STAIN can be topcoated with most clears.

MAX. VOC: 550 grams/liter (4.6 lbs./gal.)

### **CONTAINS PETROLEUM DISTILLATE.**

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.** FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

### **Limited Warranty**

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041