

1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com


PRODUCT INFORMATION

PENETRATING SEALER

PRODUCT NO.	92601, 92604, 92605, 92608
GENERIC TYPE	Sealer
COLOR	Clear
GLOSS	Not applicable
SOLIDS BY WEIGHT	53 to 54%
SOLIDS BY VOLUME	48 to 49%
V.O.C.	400 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	782 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	7.1 to 7.2 lbs.
FLASH POINT	102°F Tag Closed Cup
USE	Seals wood, metal masonry and concrete.
VISCOSITY AT 77°F	30 to 35 sec. #2 Ford Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	18 hours
RECOMMENDED THINNER	Do not thin.
APPLICATION	Brush, roller or sprayer.
SURFACE PREPARATION	On wood, sand if necessary and remove dust. Metal must be free of rust and loose particles. Masonry must be free from loose particles.
CLEAN UP	Mineral spirits. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

PENETRATING SEALER

DESCRIPTION: OLD MASTERS® PENETRATING SEALER, a clear, penetrating coating formulated with tung oil, protects and seals all types of surfaces including wood, masonry, and concrete. PENETRATING SEALER produces excellent results on interior surfaces such as floors, furniture, wall paneling, children's furniture, toys, doors, counters, tabletops, and cabinets. PENETRATING SEALER also provides excellent results on exterior surfaces such as siding, boats, railings, patio furniture, exterior doors, and soffits. PENETRATING SEALER is an ideal sealer coat for any subsequent clear coating or paint film, or for use over wood stains. On wood surfaces, PENETRATING SEALER seals out moisture to enhance the life and natural appearance of wood while preventing staining and checking. On masonry and concrete, PENETRATING SEALER produces a moisture block that reduces concrete dusting, staining, and efflorescence of masonry and brick surfaces. PENETRATING SEALER hardens masonry and natural rock surfaces and reduces frost damage. PENETRATING SEALER does not produce a film to flake or peel. Due to the slight ambering effect, do not use on white or light colored masonry surfaces.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION AND APPLICATION: All surfaces must be clean, dry, and free from dirt, wax, or grease. **WOOD SURFACES:** Sand bare wood if necessary and remove dust. Apply two or more liberal coats of PENETRATING SEALER, depending on porosity of the wood, at 10 to 15 minute intervals. Allow the final coat to stand 10 minutes, then wipe off excess sealer. Apply desired finish coat after surface has dried 12 to 18 hours. When used as an exterior finish coat, do not build an excessive film. **MASONRY SURFACES:** Remove all loose particles by wire brushing. Neutralize new concrete, masonry, stucco, or brick prior to application of PENETRATING SEALER. Excessive stains or grease-spotted surfaces should be thoroughly cleaned before applying sealer. Apply liberal coats as required. Allow 10 to 15 minutes for penetration, and remove excess material.

SPREADING RATE: Approximately 300 to 600 square feet per gallon.

DRYING TIME: Allow 12 to 16 hours drying time prior to top-coating. High humidity, low temperature, or lack of air movement will extend drying time.

CLEAN UP: Clean up with mineral spirits.
MAX. VOC: 400 grams/liter (3.3 lbs/gal)

CAUTION!

COMBUSTIBLE.

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041